



Hot Desk Display Panels





1.54"



2.13"



2.66"



2.9"

Model	RM-E154	RM-E213	RM-E266	RM-E290
Dimension (millimeter : mm)	36 x 46 x 14 mm 27 x 27 mm (screen)	68 x 35 x 14 mm 49 x 24 mm (screen)	87 x 43 x 13 mm 60 x 30.7 mm (screen)	91 x 41 x 14 mm 67 x 29 mm (screen)
Display Color & Lifetime	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable
Communication	BLE 5.0	BLE 5.0	BLE 5.0	BLE 5.0
Working Environment	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C
Others	LED light, IP65, NFC (optional)	LED light, IP65, NFC (optional)	LED light, NFC (optional)	LED light, IP67, NFC (optional)





4.2"



5.8"



7.5"



11.6"

Model	RM-E420	RM-E580	RM-E750	RM-E116
Dimension (millimeter : mm)	99 x 94 x 14 mm 85 x 64 mm (screen)	136 x 118 x 16 mm 119 x 88 mm (screen)	183 x 129 x 16 mm 163 x 98 mm (screen)	271.8 x 196 x 14 mm 244.5 x 163 mm (screen)
Display Color & Lifetime	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable	Black / White / Red 5 years (5 updates/day) Battery replaceable
Communication	BLE 5.0	BLE 5.0	BLE 5.0	BLE 5.0
Working Environment	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C
Others	LED light , IP67 , NFC (optional)	NFC optional, LED light IP65	NFC optional, LED light IP65	NFC optional, LED light IP65





**Bidirectional WiFi
Bluetooth Gateway between
Screen Panel & Cloud, connect
by Wi-Fi or Ethernet / PoE**

Size

Ø150×36mm

Materials

ABS + PC

Communication

BLE 5.0, PoE

Coverage Area

Up to 300 m. (Open Space)
or within 350 m²

Scalability

Support up to
3,000 endpoints

Maintenance

Supports firmware update
over the air

Compatibility

Roomminister Platform

