


DS-D4260FO-CLF/C
P6 Outdoor Fixel LED Display Unit



- Support rear maintenance
- Using aluminum chassis, good heat dissipation and can work under 60 °C
- All series aluminum profile cabinets support IP67(F)/IP66(R)
- Apply unique technology, maximally saving 50% energy
- Various cabinet sizes, applying to diverse scenes
- The cabinets support customized 45° corner cut to realize 90° right-angle splicing

▪ Specification

| Model | | DS-D4260FO-CLF/C |
|------------------------|--------------------------------|--|
| Cabinet | Pixel Configuration | 1R1G1B |
| | Pixel Pitch Category | P6.67 |
| | Pixel Pitch | 6.67mm |
| | Modules Component | Aluminum Shell |
| | Dimensions (W × H × D) | 120 mm × 960 mm × 127 mm (4.73" × 37.8" × 5.00") |
| | Resolution | 18 × 144 |
| | Area | 0.1152 |
| | Weight | 5 KG/PCS |
| | Pixel Density | 2592/cabinet |
| | Lamp Board Housing | YES |
| | Cabinet Material | Aluminum Profile |
| | Maintenance Method | Back Maintenance |
| | Cabinet Flatness | 0.8 mm |
| | Protection Level | IP67(F)/IP66(R) |
| Display | White Balance Brightness | 6000 |
| | Color Temperature | 3000 K to 10000 K |
| | Viewing Angle | 160° (H)/80° (V) |
| | Contrast Ratio | 8000:1 |
| | Color Uniformity | ≥ 95% |
| | Brightness Uniformity | ≥ 95% |
| Processing Performance | Driving Method | Constant Current |
| | Frame Frequency | 50/60 HZ |
| | Refresh Rate | 3840 |
| | Grey Level | 14 bit |
| | Display Color | DCI-P3 > 85% |
| Power | Power Supply | 110 to 220 |
| | Max. Consumption | 580 |
| | Average Consumption | 200 |
| Working Environment | Working Temperature | -40 to 60 °C |
| | Working Humidity | 10% to 95% RH (non-condensing) |
| | Storage Humidity | 10% to 95% RH (non-condensing) |
| | Storage Temperature | -40 to 80 °C |
| General | Gross Weight | 10 |
| | Package Dimensions (W × H × D) | 1040 mm × 160 mm × 200 mm |
| | Lifespan | 100000 Hours |

▪ Available Model

DS-D4260FO-CLF/C