

## DS-K2600T Series Access Controller

The DS-K2600T series access controller contains network and RS-485 interface, which supports TCP/IP and RS-485 communication protocols. The communication data is encrypted to improve the security of the system. The controller also supports offline operation and is designed with tamper-proof switch.



### Available Models

- DS-K2601T (Single-Door Access Controller)
- DS-K2602T (Two-Door Access Controller)
- DS-K2604T (Four-Door Access Controller)

### Features


- 32-bit high-speed processor
- Supports TCP/IP communication, EHome 5.0, and ISAPI protocol. The communication data is specially encrypted to relieve the concern of privacy leak
- User-centered design. Supports adding various user types: normal user, visitor, and user in blacklist
- Supports recognition and storage of card No. with maximum length of 20
- Supports up to 100,000 cards (including 97,000 non visitor cards and 3,000 visitor cards) and 300,000 card presenting records
- Supports multi-door interlock function, anti-passback function, multiple authentications function, open door with first card function, super card and super password function, M1 card encryption, online upgrade function and remote control of the doors
- Supports tampering alarm for the card reader, alarm for door not secured, force opening door alarm, alarm for door opening timeout, duress card and code alarm, blacklist alarm and alarm for illegal card swiping attempts reaching the limit
- Short circuit attempts alarm and open circuit attempts alarm
- IP address conflict detection
- Cross-controller anti-passback function (For cross-controller anti-passback based on card, wire the card reader with RS-485. For cross-controller anti-passback based on network, make sure the server and device communicate with each other properly. Up to 5000 users' records can be stored in the selected server.) and inner-device anti-passback function
- Supports RS-485, OSDP, and Wiegand protocol for accessing card reader. Wiegand interface supports W26, W34 and is compatible with the third-party card reader with Wiegand interface

- Supports various card types: normal/patrol/duress/super card, etc.
- Various indicators to show different status
- Supports automatically and manually time synchronization
- Supports record storage function when the device is offline and insufficient storage space storage alarm function
- Backup battery design, watchdog design and tamper-proof function
- Data can be permanently saved after the access controller is powered off
- Supports I/O linkage and event linkage
- 500 groups of password under the authentication mode of card or password
- Supports time zone settings

## Specifications

Model	DS-K2601T	DS-K2602T	DS-K2604T
Power supply	100 ~240 VAC		
Power consumption (with Load)	≤ 50 W	≤ 100 W	≤ 100 W
Power consumption (Without Load)	≤ 4 W		
Processor	32-bit		
Storage	32 M		
Communication	TCP/IP, RS-485, Wiegand (W26/W34)		
Capacity	100,000 cards 300,000 events		
LED Indicator	Power supply status, communication status, and work status		
Built-in Clock	Support		
Accessible Card Reader	2 card readers (RS-485 interface), and 2 card readers (Wiegand interface)	4 card readers (RS-485 interface), and 4 card readers (Wiegand interface)	8 card readers (RS-485 interface), and 4 card readers (Wiegand interface)
Input interface	Alarm input × 4, door contact × 1, exit button × 1, case input × 2, tamper alarm × 1	Alarm input × 4, door contact × 2, exit button × 2, case input × 4, tamper alarm × 1	Alarm input × 4, door contact × 4, exit button × 4, case input × 8, tamper alarm × 1
Output interface	Lock relay × 1, alarm relay × 2	Door relay × 2, alarm relay × 4	Lock relay × 4, alarm relay × 4
Working temperature	-20 °C to +65 °C (-4 °F to +149 °F)		
Working humidity	10% to 90% (Non-condensing)		
Dimensions (L × W × H)	373 mm × 345 mm × 98 mm (14.7" × 13.6" × 3.6")		
Approval	CE, FCC, CB		

## Typical Application



## Dimensions

