

**DS-K3G411LX  
Tripod Turnstile**

The DS-K3G411LX series tripod turnstile is designed to detect unauthorized entrance or exit. By adopting the turnstile integratedly with the access control system, It is widely used in attractions, stadiums, construction sites, residences, etc.

- Easy integration of any third-party access control system via relay input.
- Bidirectional (Entering/Exiting) lane
- LED indicates the entrance/exit and passing status.
- Fire alarm passing: When the fire alarm is triggered, the arm will be dropped automatically for emergency evacuation.
- Valid passing duration settings: System will cancel the passing permission if a person does not pass through the lane within the valid passing duration
- With key buttons to configure turnstile's functions and parameters offline.

## ▪ Specification

System	
Motor	N/A
MCBF	> 3 million times
Interface	
Exit button	2
Alarm input	1
TAMPER	NA
General	
Throughput	More than 35 persons per minute The actual throughput is affected by the person passing rate and passing method.
Lane width	550mm
Barrier material	SUS304 stainless steel
Pedestal material	SUS304 stainless steel
Built-in access controller	No
Power supply	Switching power supply: 100 to 240 VAC; 50 to 60 Hz Power adapter: 100 to 240 VAC; 50 to 60 Hz
Power consumption	Standby: 40W
Working temperature	Switching power supply: -20 °C to 65 °C (-4 °F to 149 °F) Power adapter: -10 °C to 45 °C (14 °F to 113 °F)
Working humidity	0% to 95% (No condensing)
Dimensions	Without package: 502 mm × 202 mm × 1010 mm (19.8" × 8.0" × 40.0") With package: 745 mm × 365 mm × 1120 mm (29.3" × 14.4" × 44.1")
Weight	Without package: 26 kg (57.3 lb) With package: 31 kg (68.41 lb)
Application environment	Indoor

## ▪ Available Model

DS-K3G411LX-R/Pg-Dm55/adapter,DS-K3G411LX-R/Pg-Dm55,DS-K3G411LX-R/Dm55/adapter

▪ **Dimension**

