

**DS-K6301X-DT  
Payment Terminal**

DS-K6300X-DT payment terminal is a high-performance payment product based on face recognition. Based on deep-learning algorithm, this product equips with an 8-inch IPS touch screen and a 4.3-inch IPS display screen, supporting payment via card, face, which can be widely used in business canteens.

- Dual-screen design: main screen (for consumer): 8-inch IPS touch screen, with screen resolution of 800 × 1280; sub screen (for operator): 4.3-inch IPS display screen, which screen resolution of 480 × 272
- 2 MP wide-angle lens
- Supports payment via face (face with mask supported) or card
- Supports unfixed amount, fixed amount and fixed times payment mode
- Entering unfixed amount for every payment is available
- Supports setting fixed amount for payment under fixed amount mode. Max. amount can be set for every payment
- Supports viewing payment statistics, including times, amount and etc.
- Supports management via device menu and web client, allowing payment configuration, system maintenance and other operations
- Supports wiring bluetooth speaker to amplify sound
- Supports online payment

## ▪ Specification

System	
Operating system	Android 11
Display	
Screen size	Main screen (for consumer): 8-inch Sub screen (for operator): 4.3-inch
Operation method	Main screen (for consumer): touch screen Sub screen (for operator): display screen
Type	IPS
Resolution	Main screen (for consumer): 800 × 1280 Sub screen (for operator): 480 × 272
Video	
Lens	2
Resolution	2 MP
Video standard	PAL (Default) and NTSC
Audio	
Audio input	Not support
Audio output	Built-in loudspeaker
Network	
Wired network	1, RJ-45
Wi-Fi	Support, 2.4 G, 802.11b/g/n
Interface	
Network interface	1
Alarm input	Not support
Alarm output	Not support
USB	1 type-C interface
Capacity	
Face capacity	100,000
Card capacity	500,000
Event capacity	500,000
Authentication	
Face recognition distance	0.3 m to 1.2 m
Face recognition accuracy rate	≤ 99%
Face recognition duration	< 0.2 s
Card type	M1 card, DESfire card, Felica card
Card reading distance	0 cm to 5 cm
Function	
Video intercom	Not support
QR code recognition	Reserved
Face anti-spoofing	Support
Time synchronization	Support
General	
Supplement light	IR supplement light
Power supply	12 VDC to 16 VDC

Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	0 to 90% (no condensing)
Dimensions	172.9 mm × 387.9 mm × 261 mm (6.8" × 15.3" × 10.3")
Weight	2.3 kg (5.1 lb)
Application environment	Indoor
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Chinese Traditional

▪ **Available Model**

DS-K6301X-DT

▪ **Dimension**

