



Multi-Technology Dual High Frequency Cards



AVAILABLE IN ICLASS® OR ICLASS SE® / MIFARE® CLASSIC COMBINATION AND ICLASS OR ICLASS SE / MIFARE® DESFIRE® EV1 COMBINATION

- **Ideal Migration Solution** – Mutual use of 13.56 MHz read/write iCLASS®/iCLASS SE®, MIFARE® Classic and MIFARE® DESFire® EV1 contactless smart card technologies
- **Wide Variety of Applications** – Physical access control, biometrics, secure computer/network authentication, time and attendance, vending and more
- **ISO Standard Thickness** – Use with all direct imaging and thermal transfer printers
- **Security** – Upgradable to next generation iCLASS SE platform: iCLASS SE, SIO-Enabled for MIFARE Classic and MIFARE DESFire EV1

For customers looking to support multiple technologies with a single card or migrate from existing card technology to a more secure solution, dual high frequency Genuine HID™ card products deliver an ideal solution and migration path. These affordable and durable card products enable more flexibility than ever before through the mutual use of 13.56 MHz read/write iCLASS®/iCLASS SE®, MIFARE® Classic or MIFARE® DESFire® EV1 contactless smart card technologies for credential-based applications.

with HID Prox® or magnetic stripe technology to provide the widest range of backwards compatibility with existing systems. HID Global can also embed a wide range of commercially available contact chips, or customers can select HID's off-the-shelf Crescendo® multi-technology smart card, providing strong authentication options with logical access systems.

As with all Genuine HID® card products, dual high frequency cards are part of the broadest product line of trusted, fully interoperable secure identity solutions in the market and come with guaranteed compatibility with HID Global reader lines and a lifetime warranty.



Card configurations are also available with an embeddable contact chip module to support logical access.

In addition to the two high frequency technology options, all cards are available



iCLASS*

- 13.56 MHz read/write contactless smart card provides high speed, reliable communications with high data integrity, ensuring high security with mutual authentication, encrypted data transfer and 64-bit diversified keys for read/write capabilities
- Card data protected by triple DES encryption (base parts 242,243,262,263)
- Meets ISO 15693 standards for contactless communications
- 32 Kb standard (2 Kb available with 1 KB MIFARE only)
- Multi-Layered Security - Supports data authenticity and privacy through the multi-layered security of HID's SIO (iCLASS SE base parts 391 and 396)

MIFARE* Classic

- MIFARE Classic offers fast and convenient transactions and is used worldwide for access control, cashless vending and public transportation applications
- MIFARE Application Directory (MAD) allows flexible programming of additional applications to the MIFARE Classic card
- MIFARE Classic technology uses a mutual authentication and data encryption with a 32 or 56 bit serial number
- 1 KB or 4 KB Standard options available (1 KB available with 2KB iCLASS/iCLASS SE)
- Multi-Layered Security - Supports data authenticity and privacy through the multi-layered security of HID's SIO (base parts 391 and 396)

* MIFARE DESFire EV1 is not compatible with the PIV read application used with a DESFire 0.6 card

MIFARE* DESFire* EV1

- MIFARE DESFire EV1 is based on open global standards for security, and is interoperable with existing MIFARE DESFire infrastructures*
- Transaction times are less than 100 milliseconds for a typical secure ticketing transaction
- MIFARE DESFire EV1 is fully compliant with ISO 14443A 1-4, and has been awarded CC EAL 4+ for card security
- 8 KB of dynamic memory is arranged in easy-to-define application folders and data files. Includes a test reader, test cards and documentation to speed the development
- 56 bit serial number
- Multi-Layered Security - Supports data authenticity and privacy through the multi-layered security of HID's SIO (base parts 391 and 396) process

SPECIFICATIONS

	Dual HF Technologies (iCLASS/iCLASS SE, MIFARE Classic or MIFARE DESFire EV1)	Dual HF Technologies (iCLASS, MIFARE Classic, or MIFARE DESFire EV1) - Embeddable	Dual HF Technologies (iCLASS/iCLASS SE, MIFARE Classic or MIFARE DESFire EV1) with Prox	Dual HF Technologies (iCLASS, MIFARE Classic, or MIFARE DESFire EV1) with Prox - Embeddable
Base Part Number*	PET/PVC - 242 PET/PVC - 391 (iCLASS SE)	PET/PVC - 243	PET/PVC - 262 PET/PVC - 396 (iCLASS SE)	PET/PVC - 263
Typical Maximum Read Range	iCLASS/iCLASS SE 2Kb 2Kb/32Kb: 2 - 3" • MIFARE Classic 1KB/4KB: 1 - 3" • MIFARE DESFire EV1 8KB: 1 - 2" • HID Proximity: 2 - 5"			
Dimensions	2.127" x 3.375" x 0.033" max (5.40 x 8.57 x 0.084 cm)			
Construction	100% PVC (232) 60% PET/40% PVC (242)	60% PET/40% PVC	100% PVC (232) 60% PET/40% PVC (242)	60% PET/40% PVC
Operating Temperature	-40° to 158° F (-40° to 70° C)			
Weight	0.24 oz (6.8g)	0.28 oz (7.9g)	0.24 oz (6.8g)	0.28 oz (7.9g)
Memory Size/ Application Areas	iCLASS/iCLASS SE 2Kb: 2 Kb with 2 application areas or 32 Kb with (16k/2 and 16k/1) or (16k/16 and 16k/1) MIFARE Classic: 1 KB (8Kb) arranged in 16 sectors or 4 KB (32Kb) arranged in 40 sectors MIFARE DESFire EV1: 8 KB arranged in up to 28 applications, with up to 32 files per application			
Write Endurance	Min 100,000 cycles			
Data Retention	Min 10 years			
HID Proximity	No	No	Yes	Yes
Contact Smart Chip Embeddable	No	Yes	No	Yes
Magnetic Stripe	Optional			
Printable	Yes (white/white card)			
Standard HID Artwork	Optional			
Slot Punch	Not Available (Dual HF cards do not allow a slot punch)			
Visual Security Options	Optional			
Additional Security Options	Corporate 1000, iCLASS Elite (iCLASS only)			
Warranty	Lifetime	Lifetime (Card body only)	Lifetime	Lifetime (Card body only)

© 2024 HID Global Corporation. All rights reserved. HID, the HID logo and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks and product or service names are trademarks or registered trademarks of their respective owners. 2024-06-05-hid-dual-hf-cards-ds-en PLT-00177



hidglobal.com

North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

ผู้นำเข้าอย่างเป็นทางการในประเทศไทย

บริษัท เบนนิซิส จำกัด

117/8 ซอยแจ้งวัฒนะ 10 ถนนแจ้งวัฒนะ แขวงทุ่งสองห้อง เขตหลักสี่ กรุงเทพมหานคร 10210
โทรศัพท์ +66-2-094-0800 www.bainisis.com

