



**NEXT-GENERATION HIGH-FREQUENCY CONTACTLESS SMART CARD**

- **Supports Secure Identity Object™ (SIO)** – Multi-layered security beyond the card technology, providing added protection to identity data.
- **Trusted Identity Platform™ (TIP™) enabled** – Provides trusted identity within a secure ecosystem of interoperable products.
- **Supports future growth** – iCLASS® 13.56 MHz read/write contactless smart card technology with multiple, securely separated files enables multiple applications for future growth.
- **Durable** – Cost effective card package with an ABS shell construction for durability in harsh environments.

**HID Global SIOs deliver three key benefits: portability, security and extensibility.**

- SIOs are defined using open standards that can support any piece of data, including data for access control, biometrics, PC logon, and many other applications.

A diagram showing a 'SECURE IDENTITY OBJECT' (SIO) as a red circular seal with the text 'SECURE IDENTITY OBJECT', 'KEY DIVERSIFICATION', 'AUTHENTICITY SIGNATURE', and 'ENCRYPTED ACCESS CONTROL DATA'. This seal is shown interacting with a 'STANDARD SMART CARD SECURITY' component, which is represented as a grey rectangular block with an arrow pointing from the SIO to the card.

Building on the success of the flagship iCLASS standard for 13.56 MHz contactless smart card technology, HID Global's new access control platform goes beyond the traditional smart card model to offer a secure, standards-based, technology-independent and flexible identity data structure based on Secure Identity Object (SIO), a new HID portable credential methodology.

iCLASS SIO-Enabled (iCLASS SE) smart cards are part of the next-generation iCLASS SE access control platform and open ecosystem based on HID's Trusted Identity Platform (TIP) architecture for advanced applications, mobility and heightened security. iCLASS was specifically designed to make access

control more powerful, more versatile, and more secure, with encryption for all radio frequency data transmission between the credential and reader using a secure algorithm. iCLASS SE extends this technology by providing additional key diversification, authentication, encryption and portability for advanced security and performance.

HID's iCLASS SE Clamshell is a 13.56 MHz read/write contactless smart card with an ABS shell construction for durability in harsh environments that can be used for diverse applications (physical access control, PC logon, biometric verification, time and attendance, cashless vending, public transportation, airline ticketing and customer loyalty programs).

### iCLASS® SE™ SMART CARD TECHNOLOGY FEATURES

- 13.56 MHz read/write contactless smart card technology for high-speed, reliable communications with high data integrity.
- Proven Technology - Offers consistent read range not affected by body shielding or variable environmental conditions.
- Multiple securely separated application areas are each protected by 64-bit diversified read/write keys that allow complex applications and provide for future expansion.
- Durability - Passive, no-battery design allows for an estimated minimum 100,000 reads. Strong, flexible, and resistant to cracking and breaking.
- PVC Overlay - Allows for on-site photo ID production using most direct image printers.
- Meets ISO 15693 for contactless communications.

### HIGHER SECURITY

- Trusted Identity Platform (TIP) Enabled - Provides trusted identity within a secure ecosystem of interoperable products.
- Multi-Layered Security -- Supports data authenticity and privacy through the multi-layered security of HID's SIO.
- SIO Data Binding - Inhibits data cloning by binding an object to a specific credential.
- Mutual authentication, encrypted data transfer, and 64-bit diversified keys for read/write capabilities.
- Expanded iCLASS Elite™ Program - Extends private security by protecting uniquely keyed credentials, SIOs and programming update keys.

## SPECIFICATIONS



<b>Base Part Number</b>	3350
<b>Configurations</b>	Available in 2k bit (256 Byte) configuration
<b>Card Construction</b>	ABS Shell with PVC Cover Label
<b>Dimensions</b>	2.125" x 3.375" x 0.070" max. (5.40 x 8.57 x 0.18 cm)
<b>Weight</b>	0.24 oz (6.8 g)
<b>Operating Temperature</b>	-40° to 160° F (-40° to 70° C)
<b>Operating Humidity</b>	5-95% non-condensing
<b>Operating Frequency</b>	13.56 MHz
<b>RF Interface</b>	ISO 15693 read/write
<b>Transaction Time</b>	<100 ms typical
<b>Baud Rate</b>	26 Kbps
<b>Memory Type</b>	EEPROM, read/write
<b>Multi-application Memory</b>	2k bit (256 Byte) card - 2 application areas
<b>Write Endurance</b>	Min. 100,000 cycles
<b>Data Retention</b>	10 years
<b>Typical Maximum Read Range</b>	R10: 1.5-2.5" (3.8-6.3 cm); R30/RW300: 1.5-3.0" (3.8-7.6 cm); R40/RW400: 2.5-4.5" (5.1-10.2 cm); RK40/RWK400: 3.0-4.0" (6.3-8.9 cm). *Dependent upon installation conditions.
<b>Companion Products</b>	1321 Photo pouch overlay 1324 PVC Direct print overlay
<b>1324 PVC Direct print overlay</b>	Operates with any reader that can read iCLASS technology.
<b>Warranty</b>	Lifetime warranty. See complete warranty policy for details.

© 2024 HID Global Corporation. All rights reserved. HID, the HID logo, iCLASS SE, iCLASS, Secure Identity Object and iCLASS Elite are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2024-03-11-i-class-se-clamshell-card-ds-en PLT-00226



[hidglobal.com](https://www.hidglobal.com)

North America: +1 512 776 9000  
Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 5081 1650

ผู้นำเข้าอย่างเป็นทางการในประเทศไทย

บริษัท เบนนิซิส จำกัด

117/8 ซอยแจ้งวัฒนะ 10 ถนนแจ้งวัฒนะ แขวงทุ่งสองห้อง เขตหลักสี่ กรุงเทพมหานคร 10210  
โทรศัพท์ +66-2-094-0800 [www.bainisis.com](http://www.bainisis.com)

