

# MIFARE® DESFire® EV3 + iCLASS® + Prox Card

Migrate to the most feature-rich implementation of DESFire EV3 available.

HID Global's DESFire EV3 + iCLASS+ Prox Card is designed to give security system owners the ability to add DESFire EV3 to their existing iCLASS base while adding a smooth migration path from legacy low-frequency 125 kHz-based systems to a secure credential technology.

DESFire EV3 is the latest addition to the MIFARE DESFire family of smart card chipsets from NXP. This latest evolution introduces the option of even more features for implementation, and HID has taken full advantage. Unlike many other DESFire solutions available on the market, HID's DESFire EV3 + iCLASS + Prox Card leverages these security features including AES128 encryption, secure channel-based file transfer and proximity check to protect card data from attack.

Triple tech credentials maintain interoperability with legacy 125 kHz readers and iCLASS readers, meaning that all readers do not need to be upgraded immediately when starting a migration. This enables you to smooth out the implementation and cost of the upgrade over a time frame that works best for your schedule and budget.

## PICK THE EV3 PROFILE THAT BEST MEETS YOUR NEEDS



**832 - Security** — Adopt HID's most advanced security features with its Signo readers.

**831 - Compatibility** — Maintain backwards compatibility with iCLASS SE® / multiCLASS® SE readers

**830 - Custom** — Decide for yourself which features suit your solution best

## ORDERING INFORMATION

For full details, refer to the [Readers and Credentials How to Order Guide](#).



## KEY FEATURES

- **Feature-rich security** — Secure card data with the best implementation of the DESFire EV3 toolbox including AES128 encryption, secure channel-based file transfer and proximity check to protect against man-in-the-middle attacks
- **Added assurance** — Available with the portable Secure Identity Object™ (SIO) data model for added key diversification, authentication signatures and encryption
- **Fully backwards compatible** — Protect your investment in legacy DESFire credentials and readers. EV3 credentials offer full backwards compatibility with EV1 and EV2 based solutions.
- **Simplified, cost-effective migrations**
- **Support for an ecosystem of applications and use cases** beyond physical security

MIFARE DESFire EV3 + iCLASS 32K + Prox Card			
	High Security Profile	Compatibility Profile <sup>1</sup>	Custom Profile
<b>Base Part</b>	832	831	830
<b>Operating Frequency</b>	13.56 MHz + 125kHz		
<b>Communication Protocol Compliance</b>	ISO14443A-4, up to 848kbps (DESFire) / ISO15693 (iCLASS)		
<b>Memory Type &amp; Applications</b>	DESFire: 8K, unlimited applications within memory constraint; iCLASS: 32k (16k/16 + 16k/1) or 32k (16k/2 + 16k/1)		
<b>DESFire Access Conditions</b>	Create Application Allowed <sup>2</sup>	Create Application Allowed <sup>2</sup>	User Defined <sup>3</sup>
<b>DESFire SIO Data Object Support</b>	Yes (enabled by default)	Yes (enabled by default)	Optional <sup>3</sup>
<b>DESFire HID Format Support</b>	Yes (wrapped in SIO)	Yes (wrapped in SIO)	Optional <sup>3</sup> or Unprogrammed
<b>DESFire Data Retention</b>	Minimum of 25 years		
<b>DESFire Extended Privacy Support</b>	Yes	No	Optional <sup>3</sup>
<b>DESFire SIO Application Security Features</b>	AES-128 crypto / Enhanced Secure Channel / Proximity Check	2TDEA crypto/MAC Communication	Choose from EV1, EV2 or EV3 NXP Specification <sup>3</sup>
<b>DESFire SIO Application Key Diversification</b>	Based on NIST 800-108 (CMAC/AES in Counter Mode)	Based on NIST SP800-108 (HMAC/SHA-1)	Optional <sup>3</sup>
<b>DESFire UID</b>	Random 4-byte UID	7-byte Static UID	7-byte Static / 4-byte Random UID
<b>iCLASS Format Support</b>	SIO, SIO + HID Access Application and HID Access Application		
<b>125kHz Format Support</b>	Supports HID Prox and Indala Formats		
<b>DESFIRE EV3 COMPATIBILITY &amp; PERFORMANCE<sup>4,8</sup></b>			
<b>HID Signo Readers</b>	SIO Read, EV3 Application Up to 5cm (1.97") (FW 10.0.2.2 or higher required)	SIO read, EV1 Application Up to 5cm (1.97")	Custom Data <sup>5</sup> Up to 5cm (1.97")
<b>iCLASS SE / multiCLASS SE / pivCLASS Readers</b>	Not Compatible	SIO Read, EV1 Application Up to 5cm (1.97")	Custom Data <sup>6</sup> Up to 5cm (1.97")
<b>CP1000D Desktop Encoder</b>	Not Compatible	EV1 SIO Application R/W	EV1 Application Custom Data Read / Write
<b>HID Signo Biometric Reader 25B/ iCLASS SE RB25F Fingerprint Reader</b>	Not Compatible		
<b>OMNIKEY Readers Embedded SE Devices</b>	Not Compatible	SIO Read, EV1 Application <sup>7</sup>	DESFire Custom Data <sup>7</sup>
<b>iCLASS COMPATIBILITY &amp; PERFORMANCE<sup>4,8</sup></b>			
<b>HID Signo Readers</b>	SIO or iCLASS Application read up to 15cm (5.9")		
<b>iCLASS SE / multiCLASS SE / pivCLASS Readers</b>	SIO or iCLASS Application read up to 10cm (3.94")		
<b>CP1000 Desktop Encoder</b>	SIO or iCLASS Application Programming		
<b>HID Signo Biometric Reader 25B/ iCLASS SE RB25F Fingerprint Reader</b>	Not Compatible		
<b>OMNIKEY and Embedded SE Devices</b>	SIO or iCLASS Application Read		
<b>125kHz COMPATIBILITY &amp; PERFORMANCE<sup>4,8</sup></b>			
<b>HID Prox / Indala Readers</b>	Up to 16cm (5.5") - model dependant		
<b>multiCLASS SE Readers</b>	Up to 4cm (1.6") - model dependant		
<b>HID Signo Readers</b>	Up to 5 cm (2") - model dependant		
<b>CP1000 Desktop Encoder</b>	HID Prox Read/Write		
<b>MECHANICAL, ENVIRONMENTAL AND COMPLIANCE</b>			
<b>Printing</b>	HID recommends the use of a high-definition printer (HDP) for this card		
<b>Card Construction</b>	Composite construction (40% PVC, 60% PET)		
<b>Weight</b>	~ 0.2 oz (5.5g)		
<b>Operating Temperature</b>	-40° F to 158° F (-40 °C to + 70 °C)		
<b>Min/Max Storage Temperature</b>	-31° F / 122° F (-35 °C / + 50 °C) for 1000hrs		
<b>Thermal Shock</b>	-31° F to 176° F (-35 °C to + 80°C) 100 cycles (soaking time 5 min, transition time 30 s)		
<b>Chemical Resistance</b>	The card can withstand exposure to salt water (5%) salt mist, acetic acid water (5%), carbonated sodium water(5%), sugared water (10%), ethylene glycol (50%) for at least 24 hours		
<b>Standards Compliance</b>	ISO14443A-4, ISO/IEC 24727-3:2008, EN 14890-1:200		
<b>Environmental Compliance</b>	RoHS, China RoHS, REACH, Halogen Free		
<b>Warranty</b>	Lifetime Warranty		



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +353 91 506 900

Latin America: +52 55 9171 1108 For more global phone numbers click here

ผู้นำเข้าอย่างเป็นทางการในประเทศไทย

บริษัท เบนนิซิส จำกัด

117/8 ซอยแจ้งวัฒนะ 10 ถนนแจ้งวัฒนะ แขวงทุ่งสองห้อง เขตหลักสี่ กรุงเทพมหานคร 10210  
โทรศัพท์ +66-2-094-0800 www.bainisis.com

